

Ultrasky Flat Skylight Design Features

- 1. Edge to edge glass for a contemporary look
- 2. Fine line plasterboard trim for a neat internal finish
- 3. Slim aluminium surround blends seamlessly with glass
- 4. Fully insulated kerb
- 5. Click-fit clips for quick fitting first time, every time
- 6. High compression double seal gaskets
- 7. Fully insulated frame with 'Warm Frame' technology
- 8. Tapered Kerb to deliver a 4° pitch
- 9. Noise reducing glass reduces noise by up to 34dB

SURROUND COLOURS

Black, RAL 9005 – 60% Gloss White, RAL 9003 – 80% Gloss Grey, RAL 7016 = 30% Gloss

Bespoke RAL colours and special colours available



Ultrasky Flat Skylight Product Specification

SIZES

The Ultrasky Flat Skylight is designed around maximum uninterrupted sight lines and is available in a number of square or rectangular sizes ranging from 600mm x 600mm and going up 2500mm in Length (dependant on dimensions, see price list).

GLAZING

The highly thermally efficient glazing will help reduce heat loss and noise pollution, whilst letting the maximum amount of light enter your room.

Glass outer layer – 6mm Toughened Opti Neutral **Cavity** - 16mm Argon filled cavity with warm edge spacer.


Glass inner layer – 4mm or 6mm (size of roof light dependent) high performance low E toughened

Glass u-Value 1.0 Glass G-Value 0.5

Noise reducing capabilities up to 34db Available in Clear or Blue



ULTIMATE THERMAL PERFORMANCE Overall u-Value 1.2 W/m²K





MINIMALIST

Distinctive frameless glass

- · Edge-to-edge glass for a contemporary look.
- Fineline plasterboard trim for a neat internal finish.
- Slim aluminium surround blends seamlessly with glass.

EASIEST

Unique click-fit installation

- Precision click-fit installation process for quick fitting first time, every time.
- · No fiddly trims.
- . 50% faster to fit than other skylights.
- · Welded kerb and skylight can be installed together, saving time.

CUSTOMISABLE

Unbeatable range of design options

- Bespoke sizes available.
- Grey, black and white standard colours.
- Available in any RAL or special colour.
- Available in clear and blue glazing options.

WARMEST

Fully insulated core

- · Fully insulated frame with warm frame technology.
- · Optional thermally efficient kerb available.
- Overall U-Value of 1.2.

QUIETEST

Unbeatable noise reduction

- Noise reducing glass.
- Combination of 4mm and 6mm stepped units, deliver up to 34dB noise reduction.

FASTEST

Quickest installation time

- · Simple click-fit frame.
- · Waterproof kerb provides seal to skylight.
- · One step installation process for kerb and frame.

