

STRATUS ENQUIRY FORM

Email all enquiries to: sales@tcrderby.com
 Tel: 01332 208206
 Fax back to: 01332 208204
 Text or WhatsApp: 07940438419



Company:
 Account No.
 Address:

 Postcode:
 Tel:
 Fax:
 Mobile:
 Contact Name:

Important! Please note dimensions for the Stratus lantern roof are taken from the **OUTSIDE of the supporting frame.**

Required delivery date: / /
 Reference:

Quote: Order:

KERB DETAIL

Width W: mm
 Length L: mm

Width (W) & Length (L) dimension to outside of timber support frame

Standard shown here

Plasterboard (Not Supplied)

Weatherproof Membrane (Not Supplied)

Timber Section Recommended
 150mm High 100mm Wide (Not Supplied)

100mm (Ref)

Corner Fillet (Not Supplied)

SKETCH OF DESIGN (EXTERNAL VIEW)

Use the template to draw the desired rafter layout of your roof design giving your dimensions in millimetres

KERB WIDTH WILL BE ASSUMED AS 100mm UNLESS STATED OTHERWISE

We will use 0.6kn/m² to calculate the snow loading on this roof, if you need this changed please let us know.

ROOF COLOUR

External	Internal
<input type="checkbox"/> White RAL9016	<input type="checkbox"/> White RAL9016
<input type="checkbox"/> Grey RAL7016	<input type="checkbox"/> Grey RAL7016
<input type="checkbox"/> Black RAL9005	<input type="checkbox"/> Black RAL9005

BESPOKE PAINTED COLOUR

External	Internal
RAL.....	RAL.....

*Bespoke colours may be subject to additional lead times.

ROOF GLAZING

- Unglazed for 24mm units
- Clear Low-E 1.2*
- Bronze Tint Low-E 1.2*
- Active Clear 1.2*
- Active Neutral 1.2*
- Active Bronze 1.2*
- Active Blue 1.2*
- Sunshade Blue 1.0
- Ultra Grey 1.0

*U-value upgrade optional please check below if required

Upgrade to 1.0 U-value

GENERAL INFORMATION

- Roof Pitch Fixed 20°
- 24mm glazing in all lantern roofs
- Available in any RAL Colour
- All lantern roofs are supplied with Aluminium external glazing bar cappings and castings
- All lantern roofs are supplied with PVC-U internal glazing bar cappings
- Lead time for orders: 8 - 10 Days
- Any 4 way lanterns bigger than 1.5m x 1.5m are limited to use in snow load areas of up to 1.07kn/m²
- Maximum Size for contemporary Roof: Length L=3000mm / Width W=1500mm**
- Maximum Size for 2-Way lantern roof: Length L=6000mm / Width W=1500mm**
- Maximum Size for 3-Way lantern roof: Length L=6000mm / Width W=3000mm**
- Maximum Size for 4-Way lantern roof: Length L=2000mm / Width W=2000mm**
- Suggested timber support to be 100mm wide by 150mm high (not supplied with lantern roof)
- For optimum aesthetic appeal use Width W x 1.5/2/2.5 etc to obtain Length L (e.g 1400mm W x 1.5 = L 2100mm)
- Glass with at least 1.2 U-value can be used on most sizes of Stratus Lantern. Lanterns with less than 0.6m projection will require 1.0 U-value glass. Please refer to the Thermal Design Guide or a confirmed U-value of each product.

**Maximum Sizes Shown refer to External Face of Timber Support

ROOF VENT

<input type="checkbox"/> Manual - Brass pole	<input type="checkbox"/> Manual - Chrome pole
<input type="checkbox"/> Electric* - Switch operated	<input type="checkbox"/> Electric* - Thermostat & Rain Sensor
*Electric motor case colour	
<input type="checkbox"/> White	<input type="checkbox"/> Black

Lanterns require a minimum span of 1600mm to fit opening vents

The Stratus Lantern roof has been specifically designed to be fastened down to a structurally supportive upstand in a flat roof situation. It is the sole responsibility of the installing company to make sure the supporting superstructure is designed to resist the lateral loads imposed by the Stratus Lantern.

We reserve the right to alter specifications and descriptions without prior notice as part of our policy of continuous development. E&OE. Version 2.



A confirmation of the details given will be sent to you for verification. No order will be processed without this confirmation being accepted in writing.

Our conditions of sale shall apply to the sale of the goods to the exclusion of all other terms, unless agreed in writing by TCR (Derby) Ltd.